PLAYER DRIVEN. TOUR PROVEN.

PARALLEL TIP TRIMMING

THE KBS TOUR, TGI, TOUR 105, TOUR 90, C-TAPER, C-TAPER LITE AND KBS 560/580 CAN BE PURCHASED IN TAPER TIP (.355) AND PARALLEL TIP (.370). LISTED BELOW ARE THE TRIMMING INSTRUCTIONS FOR THE PARALLEL TIP SHAFTS. THIS ALLOWS THE CLUB MAKER TO ACHIEVE DIFFERENT FLEX AND PERFORMANCE.

KBS TOUR by FST

STEP 1. SELECT YOUR SHAFT AND DESIRED FREQUENCY

	SOFTEST →			STIFFEST
TOUR R FLEX, 120g	4.0 FREQ	4.5 FREQ	5.0 FREQ	5.5 FREQ
TOUR S FLEX, 130g	5.0 FREQ	5.5 FREQ	6.0 FREQ	6.5 FREQ
TOUR X FLEX, 133g	6.0 FREQ	6.5 FREQ	7.0 FREQ	7.5 FREQ

STEP 2. SHAFT TRIMMING SPECIFICATIONS

1-IRON	0"	7/8"	1 7/8"	2 7/8"
2-IRON	7/16"	1 7/16"	2 7/16"	3 7/16"
3-IRON	1"	2"	3"	4"
4-IRON	1 9/16"	2 9/16"	3 9/16"	4 9/16"
5-IRON	2 1/8"	3 1/8"	4 1/8"	5 1/8"
6-IRON	2 11/16"	3 11/16"	4 11/16"	5 11/16"
7-IRON	3 1/4"	4 1/4"	5 1/4"	6 1/4"
8-IRON	3 13/16"	4 13/16"	5 13/16"	6 13/16"
9-IRON	4 3/8"	5 3/8"	6 3/8"	7 3/8"
PW	4 15/16"	5 15/16"	6 15/16"	7 15/16"

PERFORMANCE CHART

FLEX	ACHIEVABLE RANGE
REGULAR	4.0 fm - 5.5 fm
STIFF	5.0 fm - 6.5 fm
X-STIFF	6.0 fm - 7.5 fm

KBS TOUR 90 by FST

STEP 1. SELECT YOUR SHAFT AND DESIRED FREQUENCY

	SOFTEST →		STIFFEST
TOUR 90 R FLEX, 101g	3.0 FREQ	3.5 FREQ	4.0 FREQ
TOUR 90 S FLEX, 102g	4.0 FREQ	4.5 FREQ	5.0 FREQ

STEP 2. SHAFT TRIMMING SPECIFICATIONS

4-IRON	0"	1 1/2"	3"
5-IRON	1/2"	2"	3 1/2"
6-IRON	1"	2 1/2"	4"
7-IRON	1 1/2"	3"	4 1/2"
8-IRON	2"	3 1/2"	5"
9-IRON	2 1/2"	4"	5 1/2"
PW	2 1/2"	4"	5 1/2"

PERFORMANCE CHART

FLEX	ACHIEVABLE RANGE
REGULAR	3.0 fm - 4.0 fm
STIFF	4.0 fm - 5.0 fm

KBS C-TAPER by FST

STEP 1. SELECT YOUR SHAFT AND DESIRED FREQUENCY

	SOFTEST →			STIFFEST
C-TAPER R FLEX, 125g	3.5 FREQ	4.0 FREQ	4.5 FREQ	5.0 FREQ
C-TAPER S FLEX, 135g	4.5 FREQ	5.0 FREQ	5.5 FREQ	6.0 FREQ
C-TAPER X FLEX, 140g	5.5 FREQ	6.0 FREQ	6.5 FREQ	7.0 FREQ

STEP 2. SHAFT TRIMMING SPECIFICATIONS

1-IRON	3/16"	1 3/16"	2 3/16"	3 3/16"
2-IRON	3/4"	1 3/4"	2 3/4"	3 3/4"
3-IRON	1 5/16"	2 5/16"	3 5/16"	4 5/16"
4-IRON	1 7/8"	2 7/8"	3 7/8"	4 7/8"
5-IRON	2 7/16"	3 7/16"	4 7/16"	5 7/16"
6-IRON	3"	4"	5"	6"
7-IRON	3 9/16"	4 9/16"	5 9/16"	6 9/16"
8-IRON	4 1/8"	5 1/8"	6 1/8"	7 1/8"
9-IRON	4 11/16"	5 11/16"	6 11/16"	7 11/16"
PW	5 1/4"	6 1/4"	7 1/4"	8 1/4"

PERFORMANCE CHART

FLEX	ACHIEVABLE RANGE
REGULAR	3.5 fm - 5.0 fm
STIFF	4.5 fm - 6.0 fm
X-STIFF	5.5 fm - 7.0 fm

KBS C-TAPER LITE by FST

STEP 1. SELECT YOUR SHAFT AND DESIRED FREQUENCY

	SOFTEST →	STIFFEST
C-TAPER LITE R FLEX, 108.5g	4.0 FREQ	4.5 FREQ
C-TAPER LITE S FLEX, 118.5g	4.5 FREQ	5.0 FREQ
C-TAPER LITE X FLEX, 125g	5.0 FREQ	5.5 FREQ

STEP 2. SHAFT TRIMMING SPECIFICATIONS

1-IRON	1/2"	1 1/2"
2-IRON	1"	2"
3-IRON	1 1/2"	2 1/2"
4-IRON	2"	3"
5-IRON	2 1/2"	3 1/2"
6-IRON	3"	4"
7-IRON	3 1/2"	4 1/2"
8-IRON	4"	5"
9-IRON	4 1/2"	5 1/2"
PW	4 1/2"	5 1/2"

PERFORMANCE CHART

FLEX	ACHIEVABLE RANGE
REGULAR	4.0 fm - 4.5 fm
STIFF	4.5 fm - 5.0 fm
X-STIFF	5.0 fm - 5.5 fm

KBS TOUR 560 by FST

STEP 1. ANALYSIS

	GRAPHITE	STEEL
RIGHT TO LEFT (RIGHT-HANDED)	START WITH 560 MODEL	START WITH 580 MODEL
LEFT TO RIGHT (RIGHT-HANDED)	START WITH 560 MODEL	START WITH 580 MODEL
RIGHT TO LEFT (LEFT-HANDED)	START WITH 560 MODEL	START WITH 580 MODEL
LEFT TO RIGHT (LEFT-HANDED)	START WITH 560 MODEL	START WITH 580 MODEL

STEP 2. SELECT SHAFT FLEX

	REGULAR		STIFF	

STEP 3. TIP TRIM SHAFT

	TIP TRIM (IN.)	LENGTH (IN.)	TIP TRIM (IN.)	LENGTH (IN.)
3-IRON			1"	36 1/2"
4-IRON	0"	36"	1 1/2"	36"
5-IRON	1/2"	35 1/2"	2"	35 1/2"
6-IRON	1"	35"	2 1/2"	35"
7-IRON	1 1/2"	34 1/2"	3"	34 1/2"
8-IRON	2"	34"	3 1/2"	34"
9-IRON	2 1/2"	33 1/2"	4"	33 1/2"
PW	3"	33"	4 1/2"	33"

KBS TOUR 580 by FST

STEP 1. ANALYSIS

	GRAPHITE	STEEL
RIGHT TO LEFT (RIGHT-HANDED)	START WITH 560 MODEL	START WITH 580 MODEL
LEFT TO RIGHT (RIGHT-HANDED)	START WITH 560 MODEL	START WITH 580 MODEL
RIGHT TO LEFT (LEFT-HANDED)	START WITH 560 MODEL	START WITH 580 MODEL
LEFT TO RIGHT (LEFT-HANDED)	START WITH 560 MODEL	START WITH 580 MODEL

STEP 2. SELECT SHAFT FLEX

	REGULAR		STIFF	

STEP 3. TIP TRIM SHAFT

	TIP TRIM (IN.)	LENGTH (IN.)	TIP TRIM (IN.)	LENGTH (IN.)
3-IRON			1"	36 1/2"
4-IRON	0"	36"	1 1/2"	36"
5-IRON	1/2"	35 1/2"	2"	35 1/2"
6-IRON	1"	35"	2 1/2"	35"
7-IRON	1 1/2"	34 1/2"	3"	34 1/2"
8-IRON	2"	34"	3 1/2"	34"
9-IRON	2 1/2"	33 1/2"	4"	33 1/2"
PW	3"	33"	4 1/2"	33"

KBS TOUR 105 by FST

STEP 1. SELECT YOUR SHAFT AND DESIRED FREQUENCY

	SOFTEST →	STIFFEST
TOUR 105 R FLEX, 109g	3.0 FREQ	4.5 FREQ
TOUR 105 S FLEX, 114g	4.0 FREQ	5.5 FREQ
TOUR 105 X FLEX, 119g	5.0 FREQ	6.5 FREQ

STEP 2. SHAFT TRIMMING SPECIFICATIONS

3-IRON	1"	2"
4-IRON	1 1/2"	2 1/2"
5-IRON	2"	3"
6-IRON	2 1/2"	3 1/2"
7-IRON	3"	4"
8-IRON	3 1/2"	4 1/2"
9-IRON	4"	5"
PW	4 1/2"	5 1/2"

PERFORMANCE CHART

FLEX	ACHIEVABLE RANGE
REGULAR	3.0 fm - 4.5 fm
STIFF	4.0 fm - 5.5 fm
X-STIFF	5.0 fm -6.5 fm

KBS MAX 80 by FST

STEP 1. SELECT SHAFT FLEX

REGULAR | STIFF | X-STIFF

STEP 2. TIP TRIM SHAFT

	REGULAR		STIFF		X-STIFF	
	TIP TRIM (IN.)	LENGTH (IN.)	TIP TRIM (IN.)	LENGTH (IN.)	TIP TRIM (IN.)	LENGTH (IN.)
3-IRON	1"	41"	2"	40"	3"	39"
4-IRON	1 1/2"	40 1/2"	2 1/2"	39 1/2"	3 1/2"	38 1/2"
5-IRON	2"	40"	3"	39"	4"	38"
6-IRON	2 1/2"	39 1/2"	3 1/2"	38 1/2"	4 1/2"	37 1/2"
7-IRON	3"	39"	4"	38"	5"	37"
8-IRON	3 1/2"	38 1/2"	4 1/2"	37 1/2"	5 1/2"	36 1/2"
9-IRON	4"	38"	5"	37"	6"	36"
PW	4"	38"	5"	37"	6"	36"

KBS $-TAPER LITE by FST

STEP 1. SELECT YOUR SHAFT AND DESIRED FREQUENCY

	SOFTEST		STIFFEST
$-TAPER LITE R FLEX, 110g	3.0 FREQ	3.5 FREQ	4.0 FREQ
$-TAPER LITE S FLEX, 115g	4.0 FREQ	4.5 FREQ	5.0 FREQ
$-TAPER LITE X FLEX, 120g	5.0 FREQ	5.5 FREQ	6.0 FREQ

STEP 2. SHAFT TRIMMING SPECIFICATIONS

3-IRON	1/2"	1 1/2"	2 1/2"
4-IRON	1"	2"	3"
5-IRON	1 1/2"	2 1/2"	3 1/2"
6-IRON	2"	3"	4"
7-IRON	2 1/2"	3 1/2"	4 1/2"
8-IRON	3"	4"	5"
9-IRON	3 1/2"	4 1/2"	5 1/2"
PW	3 1/2"	4 1/2"	5 1/2"

PERFORMANCE CHART

FLEX	ACHIEVABLE RANGE
REGULAR	3.0 fm - 4.0 fm
STIFF	4.0 fm - 5.0 fm
X-STIFF	5.0 fm - 6.0 fm

KBS TOUR GRAPHITE IRON by FST

	80g - 4.0 FREQ	70g - 3.0 FREQ	60g - 2.0 FREQ	50g - 1.0 FREQ
3-IRON	1/2"	1/2"	1/2"	1/2"
4-IRON	1"	1"	1"	1"
5-IRON	1 1/2"	1 1/2"	1 1/2"	1 1/2"
6-IRON	2"	2"	2"	2"
7-IRON	2 1/2"	2 1/2"	2 1/2"	2 1/2"
8-IRON	3 "	3 "	3 "	3 "
9-IRON	3 1/2"	3 1/2"	3 1/2"	3 1/2"
PW	3 1/2"	3 1/2"	3 1/2"	3 1/2"

KBS MAX GRAPHITE IRON by FST

	85g - 3.0 FREQ	75g - 2.0 FREQ	65g - 1.0 FREQ	55g - 0 FREQ	45g - -1.5 FREQ
3-IRON	1/2"	1/2"	1/2"	1/2"	1/2"
4-IRON	1"	1"	1"	1"	1"
5-IRON	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"
6-IRON	2"	2"	2"	2"	2"
7-IRON	2 1/2"	2 1/2"	2 1/2"	2 1/2"	2 1/2"
8-IRON	3 "	3 "	3 "	3 "	3 "
9-IRON	3 1/2"	3 1/2"	3 1/2"	3 1/2"	3 1/2"
PW	3 1/2"	3 1/2"	3 1/2"	3 1/2"	3 1/2"

KBS PLAYERS GRAPHITE IRON by FST

	100g - 6.0 FREQ	90g - 5.0 FREQ	80g - 4.0 FREQ	70g - 3.0 FREQ
3-IRON	1/2"	1/2"	1/2"	1/2"
4-IRON	1"	1"	1"	1"
5-IRON	1 1/2"	1 1/2"	1 1/2"	1 1/2"
6-IRON	2"	2"	2"	2"
7-IRON	2 1/2”	2 1/2”	2 1/2”	2 1/2”
8-IRON	3 "	3 "	3 "	3 "
9-IRON	3 1/2"	3 1/2"	3 1/2"	3 1/2"
PW	3 1/2"	3 1/2"	3 1/2"	3 1/2"

	60g - 2.0 FREQ	50g - 1.0 FREQ
3-IRON	1/2"	1/2"
4-IRON	1"	1"
5-IRON	1 1/2"	1 1/2"
6-IRON	2"	2"
7-IRON	2 1/2”	2 1/2”
8-IRON	3 "	3 "
9-IRON	3 1/2"	3 1/2"
PW	3 1/2"	3 1/2"